

VENTILATION SASH



VENTILATION SASH HINGES

Functions

Set of hinges (top and bottom) for side-hung or secondary sash with tilt-and-turn CHIC 3D 100.

Online data sheet




Technical Features

Sash opening to 180°. Maximum load capacity 100 kg. Assembly is simple, fast and easy using the special pre-assembled cams. When there is an additional fastening mechanism, you need to use the CHIC fastening element. Both hinges are adjustable (3D). If opening is obstructed, you need to use the FRIZ limitation arm.
CAUTION: This hinge is designed to be used only on inward opening casements and is not suitable for outward opening casements.


Materials

Corner support made of zamak
 Connecting brackets and hinge plates made of zinc plated steel
 Pins made of 304 grade stainless steel and aluminium bronze
 Cams made of zinc plated steel


ADJUSTMENTS [mm]



Height:
+2.5 / -1



Side:
+1.5 / -1.5



Hinge compression:
+1.4 / -0.6

Item code	Description	PROFILE CROSS - SECTION	Hand	Base Raw	Anodised Elox	Painted	Trend/Gold Brass	Pieces per pack
043541	CHIC - SASH HINGE SET	C001-C002-C003-C005-C006	RX	X				10
043542	CHIC - SASH HINGE SET	C001-C002-C003-C005-C006	LX	X				10